

SolarTech Power Solutions

Huawei India Energy Storage Project Company

12.8V6Ah



Nominal voltage (V):12.8
Nominal capacity (ah):6
Rated energy (WH):76.8
Maximum charging voltage (V):14.6
Maximum charging current (a):6
Floating charge voltage (V):13.6~13.8
Maximum continuous discharge current (a):10
Maximum peak discharge current @10 seconds (a):20
Maximum load power (W):100
Discharge cut-off voltage (V):10.8
Charging temperature (°C):0~+50
Discharge temperature (°C): -20~+60
Working humidity: <95% R.H (non condensing)
Number of cycles (25 °C, 0.5c, 100%dod): >2000
Cell combination mode: 32700-4s1p
Terminal specification: T2 (6.3mm)
Protection grade: IP65
Overall dimension (mm):90*70*107mm
Reference weight (kg):0.7
Certification: un38.3/msds

Overview

Huawei's energy storage project is advancing significantly, with distinct milestones achieved in 2023, expanding its global influence in renewable energy solutions, increasing partnerships with local utilities, and enhancing technological innovations to improve efficiency and reliability.

Huawei India Energy Storage Project Company

Contact Us

For catalog requests, pricing, or partnerships, please visit:
<https://www.zegrzynek.pl>