

SolarTech Power Solutions

Solar panels power generation in Ethiopia

12.8V6Ah



Nominal voltage (V):12.8
Nominal capacity (ah):6
Rated energy (WH):76.8
Maximum charging voltage (V):14.6
Maximum charging current (a):6
Floating charge voltage (V):13.6~13.8
Maximum continuous discharge current (a):10
Maximum peak discharge current @10 seconds (a):20
Maximum load power (W):100
Discharge cut-off voltage (V):10.8
Charging temperature (°C):0~+50
Discharge temperature (°C): -20~+60
Working humidity: <95% R.H (non condensing)
Number of cycles (25 °C, 0.5c, 100%dod): >2000
Cell combination mode: 32700-4s1p
Terminal specification: T2 (6.3mm)
Protection grade: IP65
Overall dimension (mm):90*70*107mm
Reference weight (kg):0.7
Certification: un38.3/msds

Overview

Reports indicate solar accounted for less than 0.5 percent of Ethiopia's total power output last year. This is despite Ethiopia's immense potential and suitability for solar power production, given its exceptionally high annual solar radiation levels.

Solar panels power generation in Ethiopia

Contact Us

For catalog requests, pricing, or partnerships, please visit:
<https://www.zegrzynek.pl>